

**Elite Acoustic – Matt**  
Technical Data & Specification Sheet  
Larkrise Coatings 6 Bolton Grove, Hartlepool TS25 1BD  
Tel: 01429 291301 www.spray-shop.co.uk

Product	Elite Acoustic-Matt stain covering, solvent based, high opacity coating for interior suspended ceilings. Acoustic Matt has been designed for use on heavy staining and contamination.
Description:	Elite Acoustic-Matt is a problem solving stain covering solvent based coating. It is self priming and has been designed to cover heavy staining including nicotine, smoke, fire damage & graffiti without the need to washing down, or priming. Acoustic Matt is without doubt the best stain blocking problem solving solvent based product on the market today. Acoustic-matt offers a 100% matt flat finish.
Where to Use:	Suspended ceilings, plasterboard, concrete, plaster, cladding, wood, existing paint films, wallpaper & galvanised.
Properties:	<ul style="list-style-type: none"><li>• Excellent stain covering, inc nicotine &amp; water stains</li><li>• Solvent based</li><li>• Flat matt uniform finish with no roller marks</li><li>• Excellent productivity</li><li>• Self priming finish coat</li><li>• Durable</li><li>• Washable</li><li>• Will not flake or peel</li><li>• Vapour permeable</li></ul>
Specification	
Preparation:	Brush down the surface to remove all dust, cobwebs etc, de-grease any heavy contamination, spot prime any bare steel or seal any wet watermarks, mask up if product to be applied by spray.
Application:	Acoustic-Matt can be applied by brush, roller or airless spray. For brush and roller application do not dilute, apply a 50 / 50 mist coat then one full coat to finish. Acoustic-Matt should remove the need for a 2nd topcoat  If applied by airless spray use a 0.13 to 0.15 tip, dilute by 5% and apply one full coat overlapping each pass by 50%. This should be sufficient. However depending on the substrate a further mist coat may be required to complete the project.
Completion:	Clean brush, roller & machine with warm water, clean area ready for re-occupation.
Tech data:	
Colour	White as standard but can be supplied in any RAL or BS colour
Solids	62%
Spread rate	6m <sup>2</sup> per litre depending on WFT Required.
Dry to touch	20 minutes
Recoat after	1.5 hours
Clean-up	Spirits
Flash Point	70°C
WFT	About 250 microns
Containers	15 litres

